



## MCCB h1000 3P 70kA 1000A LSI

HEE970H

### Architecture

Type of order	Toggle
Type of case	Fixed built-in
Number of poles	3 P
Type of pole	3P3D

### Functions

Complete device with protection unit	yes
Trip Unit	LSI
Integrated earth fault protection	no

### Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

### Controls and indicators

Motor drive integrated	no
------------------------	----

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage U <sub>e</sub>	220/690 V

### Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V
With under voltage release	no

### Electric current

Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 400V AC IEC 60947-2	70 kA
Rated service breaking capacity I <sub>cs</sub> AC according IEC 60947-2	71 %
Breaking capacity on 1 pole with 230 V NF 60947-2	60 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	9 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 230V AC IEC 60947-2	100 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 240V AC IEC 60947-2	100 kA

Technical Properties

Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	70 kA
Rated ultimate short-circuit breaking capacity Icu under 440V AC IEC 60947-2	65 kA
Rated ultimate short-circuit breaking capacity Icu under 690V AC IEC 60947-2	20 kA
Thermal protection nob setting xIN	0,4/0,5/0,63/0,8/0,9/0,95/1

**Current correction factors**

Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 1 side-by-side	
Correction factor of rating current for 4 and 5 devices 1 placed side-by-side	
Correction factor of rating current for 6 devices placed 1 side-by-side	

**Power**

Power loss per pole at In	62 W
Power loss per pole at 0.63*In	24,6 W
Power loss per pole at 0.8*In	39,7 W
Total power loss under IN	186 W
Total power loss at 0.63*In	73,8 W
Total power loss at 0.8*In	119 W

**Tripping**

Tripmode	LSI
Thermal protection trip time	5/10/11/16/21 ms
Time of response when opening	10 ms

**Electrical specifications**

Magnetic trip delay time	100 to 200 ms
--------------------------	---------------

**Endurance**

Electric endurance in number of cycles	1000
Number of mechanical operations	4000

**Installation, mounting**

Tightening torque	65Nm
DIN rail mounting with optional adaptor	no

**Connection**

Connection cross-sect. rigid cable	2x240mm <sup>2</sup>
Connection cross-sect. flexible conductor	2x240mm <sup>2</sup>
Connection	Front connection
Type of connection	Terminal

**Settings**

Magnetic protection nob setting xIN	2,5/5/8
Setting type In or Ith	IrTh
Range of the magnetic adjustment	5600/7000/8820/10000/10000/10000/10000 A

**Equipment**

Motor drive optional	yes
----------------------	-----

**Use cases**

Category of use	A
-----------------	---

**Standards**

Standard text	IEC 60947-2
European directive WEEE	concerned

**Safety**

Protection index IP	IP4X
---------------------	------

**Use conditions**

Altitude	2000 m
Storage temperature	-35 to 70 °C
Air humidity protection	for all climates