

Contactor 115A-AC3 / coil 220V 50-60Hz

Architecture

Type of pole	3 P
--------------	-----

Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

Main electrical features

Type of supply voltage	AC
Rated operational voltage Ue	690 V

Voltage

Rated insulation voltage	1000 V
Command voltage AC	220 V

Electric current

Acceptable current rating with AC1	135 A
Rated operational current in AC3	115 A
Thermal rated current outside of housings	135 A

Power

Contact rating with 400 V in AC3	60 kW
----------------------------------	-------

Endurance

Electric endurance in number of cycles	500000
Number of mechanical operations	5000000

Measurement

Relative humidity (without condensation)	45 85 %
--	---------

Dimensions

Depth of installed product	133 mm
Height of installed product	139 mm
Width of installed product	100 mm

Connection

Type of connection	Terminal
Connection cross section of access and exit with screws, for flexible conductor	25/50 mm ²
Connection cross-section of input and output with screws, for massive conductors	25/50 mm ²

Equipment

Number of auxiliary contacts as normally closed contact	2
Number of auxiliary contacts as normally open contact	2
Quantity of NO contacts	3

Use cases

Category of use	AC3
-----------------	-----

Standards

Standard text	IEC 60 947-4-1
---------------	----------------

Use conditions

Altitude	2000 m
Storage temperature	-40 to 80 °C

Identification

Device family	EW
---------------	----
