

## Systo Double socket Schuko Green

## WS172V



Arch	itecture
------	----------

Type of pole	SCHUKO
Fixing mode	universal fixing
Functions	
Overvoltage protection	no
Controls and indicators	
Indicator lamp	no
Main electrical features	
Frequency	50/60 Hz
Nominal voltage	250 V
Cover, door	
Interlockable	no
Materials	
RAL colour	RAL 6029 - Mint green
Material	Polycarbonate (PC)
Material Surface appearance	Polycarbonate (PC) matt
Material	Polycarbonate (PC)
Material Surface appearance	Polycarbonate (PC) matt
Material Surface appearance Type of surface treatment	Polycarbonate (PC) matt
Material Surface appearance Type of surface treatment  Dimensions	Polycarbonate (PC) matt Painted
Material Surface appearance Type of surface treatment  Dimensions  Depth of installed product	Polycarbonate (PC) matt Painted 42,5 mm
Material Surface appearance Type of surface treatment  Dimensions  Depth of installed product Height of installed product	Polycarbonate (PC) matt Painted  42,5 mm 45 mm
Material Surface appearance Type of surface treatment  Dimensions  Depth of installed product Height of installed product Length	Polycarbonate (PC) matt Painted  42,5 mm 45 mm 45 mm
Material Surface appearance Type of surface treatment  Dimensions  Depth of installed product Height of installed product Length Width of installed product	Polycarbonate (PC) matt Painted  42,5 mm 45 mm 45 mm 90 mm
Material Surface appearance Type of surface treatment  Dimensions  Depth of installed product Height of installed product Length Width of installed product Dimensions (LLxwwxhh)	Polycarbonate (PC) matt Painted  42,5 mm 45 mm 45 mm 90 mm

Connection cross-sect. rigid cable	1,5 / 2,5mm²
Type of connection	quick connect
Equipment	
On/Off switch	no
Standards	
Approvals	VDE
Safety	
Protection index IP	IP2X
IK protection code against mecanical impacts	07
Halogen free	yes
Identification	
Range	systo