



Push-button, 1-gang, with labelling fie

75161385

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

- for switch, push-button, dimmer and shutter functions

Compatibility

- extension unit for light scene push-button

Connectivity

- for radio wall-transmitter insert

Measurement

- dimming / position value transmitter 1 byte

Materials

RAL colour	RAL 7021 - Black grey
Colour of design line	aluminium/anthracite
Colour independent of design lines	for anthracite and aluminium
Colour	aluminium/anthracite
Material	Plastic/metal
Surface appearance	glossy
Type of surface treatment	untreated

Dimensions

Height	55,4 mm
Width	55,4 mm

LED control

- with 2 red transmission and battery status LEDs

Connection

- for bus coupling unit flush-mounted

Equipment

Product type: product type: push-button 1gang

Use

- with labelling field
- with horizontal operation

Safety

Protection index IP IP20

Halogen free no

- with dismantling protection

Use conditions

Operating temperature -5 45 °C

Identification

Application, usage Radio bus - operating systems, KNX
- operating systems

Product family product family: push-button

Main design line KNX - Berker S.1/B.3/B.7

Secondary design line(s) Berker B.3, Radio bus, Berker B.1,
KNX, Berker B.7