



Push-button, 1-gang comfort, with label

75161780

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

- for switch, push-button, dimmer and shutter functions

Compatibility

- extension unit for light scene push-button

Controls and indicators

- activation of second user level via object
- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Materials

RAL colour	RAL 1013 - Oyster white
Colour of design line	white/polar white
Colour independent of design lines	for white and polar white
Colour	white/polarwhite
Material	thermoplastic
Surface appearance	glossy
Type of surface treatment	untreated

Dimensions

Height	55,5 mm
Width	55,4 mm

LED control

- with white operation LED and 2 red status LEDs

Connection

- for bus coupling unit flush-mounted

Settings

- single and two push-button operation parameterisable

Equipment

Product type: product type: push-button 1gang

Use

- with labelling field
- with horizontal operation

Safety

Protection index IP IP20
Halogen free no

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5 45 °C

Identification

Application, usage KNX - operating systems
Product family product family: push-button
Main design line KNX - Berker S.1/B.3/B.7
Secondary design line(s) KNX, Berker B.1, Berker S.1, Berker B.7, Berker B.3