



## Push-button, 4-gang comfort, with label

75164780

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

- for switch, push-button, dimmer and shutter functions

### Compatibility

- extension unit for light scene push-button

### Controls and indicators

- one push-button operation for switching, pushing, shutters and dimming
- lockable via 3-button actuation
- second operating level via object or 3-button handle

### Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Materials

RAL colour	RAL 1013 - Oyster white
Colour of design line	white/polar white
Colour independent of design lines	for white and polar white
Colour	white/polarwhite
Material	thermoplastic
Surface appearance	glossy
Type of surface treatment	untreated

### Dimensions

Height	110,7 mm
Width	56 mm

#### LED control

- with white operation LED and 8 red status LEDs

#### Connection

- for bus coupling unit flush-mounted

#### Settings

- single and two push-button operation parameterisable

#### Equipment

Product type: product type: push-button 4gang

#### Use

- with labelling fields
- with horizontal operation

#### Safety

Protection index IP IP20  
Halogen free no

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

#### Use conditions

Operating temperature -5 45 °C

#### Identification

Application, usage KNX - operating systems  
Product family product family: push-button  
Main design line KNX - Berker S.1/B.3/B.7  
Secondary design line(s) KNX, Berker B.1, Berker B.3, Berker S.1, Berker B.7

#### Instructions

- Use only in combination with frame frame with large cut-out.