



## HBNet ZSU JAL K5 E-STAHl

85741173

### Functions

---

Power reserve	~ 24 h
---------------	--------

---

- reset function (to factory setting)
- with keylock
- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)
- with switchover manual/automatic mode

---

### Controls and indicators

- 
- LC display illuminated during operation
  - indication of the application module/insert compatibility in the display
  - LC display contrast is adjustable
- 

### Power

- 
- low intrinsic energy requirement
- 

### Measurement

---

Relative humidity (without condensation)	0 65 % (without condensation)
--	-------------------------------

---

### Detection

- 
- Not suitable for rain and wind sensors
- 

### Materials

---

Colour of design line	stainless steel
Colour	stainless steel
Material / workmanship	lacquered
Material	Plastic/metal

---

### Installation, mounting

- 
- clamp fastening
-

---

**Settings**

---

- with automatic summer-/winter time switching (can be switched off)
  - astro programme for sunrise/sundown switching with city/country or co-ordinate input, individually adaptable
  - holiday programme for random variation of the operation times in automatic operation
- 

**Equipment**

---

- 2 independent preset programme memories, individually adaptable
- 

**Use**

---

- with display
- 

**Safety**

---

- with dismantling protection
- 

**Use conditions**

---

Operating temperature -5 45 °C

---

**Identification**

---

Application, usage	Blind control
Main design line	Berker K.5

---

**Instructions**

---

- Can be switched to orientation led by extension unit.
-