



MCB 2P 3kA C-10A 2M

MW210

Architecture

| | |
|---------------------------|-----|
| Number of protected poles | 2 |
| Number of poles | 2 P |
| Type of pole | 2 P |
| Curve | C |

Connectivity

| | |
|---|------------------|
| Bottom connection alignment for modular devices | Aligned terminal |
| Top connection alignment for modular devices | Aligned terminal |

Main electrical features

| | |
|--|-----------|
| Frequency | 50/60 Hz |
| Rated short circuit breaking capacity I_{cn} AC according IEC60898-1 | 3 kA |
| Rated operational voltage U_e | 230/400 V |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 500 V |
| Rated impulse withstand voltage | 4000 V |

Electric current

| | |
|---|--------------|
| Rated short circuit breaking capacity I_{cn} under 400V AC according IEC60898-1 | 3 kA |
| Rated service breaking capacity I_{cs} AC according IEC 60898-1 | 3 kA |
| Breaking capacity on 1 pole with 400 V NF 60947-2 | 3 kA |
| Rated ultimate short-circuit breaking capacity I_{cu} under 415V AC IEC 60947-2 | 4,5 kA |
| Magnetic regulating current at 40° C | 5/10 In |
| min/maxi threshold value of the DC magnetic operation | 7/15 In |
| min/maxi threshold value of the AC thermal operation | 1,13/1,45 In |
| min/maxi threshold value of the DC thermal operation | 1,13/1,45 In |

Electric current / temperature

| | |
|----------------------|--------|
| Rating current -15°C | 12 A |
| Rating current -20°C | 12,2 A |
| Rating current 0°C | 11,4 A |
| Rating current 10°C | 10,9 A |
| Rating current -10°C | 11,8 A |
| Rating current 15°C | 10,7 A |
| Rating current 20°C | 10,5 A |
| Rating current 25°C | 10,2 A |
| Rating current -25°C | 12,4 A |
| Rating current 30°C | 10 A |
| Rating current 35°C | 9,8 A |
| Rating current 40°C | 9,5 A |
| Rating current 45°C | 9,2 A |
| Rating current 5°C | 11,2 A |
| Rating current -5°C | 11,6 A |
| Rating current 50°C | 9 A |
| Rating current 55°C | 8,7 A |
| Rating current 60°C | 8,4 A |
| Rating current 65°C | 8,2 A |
| Rating current 70°C | 7,9 A |

Current correction factors

| | |
|---|-----|
| Correction factor of magnetic tripping with 100 Hz | 1,1 |
| Correction factor of magnetic tripping with 200 Hz | 1,2 |
| Correction factor of magnetic tripping with 400 Hz | 1,5 |
| Correction factor of magnetic tripping with 60 Hz | 1 |
| Correction factor of rating current for 2 devices placed 1 side-by-side | |
| Correction factor of rating current for 3 devices placed 0,95 side-by-side | |
| Correction factor of rating current for 4 and 5 devices placed side-by-side | 0,9 |
| Correction factor of rating current for 6 devices placed 0,85 side-by-side | |

Power

| | |
|---------------------------|--------|
| Power loss per pole at In | 1,93 W |
| Total power loss under IN | 3,8 W |

Endurance

| | |
|--|-------|
| Electric endurance in number of cycles | 4000 |
| Number of mechanical operations | 20000 |

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 70 mm |
| Height of installed product | 83 mm |
| Width of installed product | 35 mm |

Installation, mounting

| | |
|---|------------|
| Type of top connection for modular devices | with screw |
| Tightening torque | 2,8Nm |
| Type of bottom rail clip for modular devices | metallic |
| Type of top rail clip for modular devices | NA |
| Type of Bottom Connection for modular devices | Blconnect |
| Bottom removability for modular devices | no |

Technical Properties

| | |
|--------------------------------------|----|
| Top removability for modular devices | no |
|--------------------------------------|----|

Connection

| | |
|--|-----------------------|
| Connection cross-sect. rigid cable | 1 / 35mm ² |
| Connection cross-sect. flexible conductor | 1 / 25mm ² |
| Type of connection | with screw |
| Connection cross section of access and exit with screws, for flexible conductor | 1/25 mm ² |
| Connection cross-section of input and output with screws, for massive conductors | 1/35 mm ² |

Standards

| | |
|-------------------------|------------|
| Standard text | EN 60898-1 |
| European directive WEEE | concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|--|------------------|
| Degree of pollution according to IEC 60664 / IEC 60947-2 | 2 |
| Operating temperature | -25 70 °C |
| Class of energy limitation I ² t | 3 |
| Altitude | 2000 m |
| Storage temperature | -25 to 80 °C |
| Air humidity protection | for all climates |
| Storage/transport temperature | -25 80 °C |