



## MCCB x160 3P 40kA 25A

HNA025Z

### Architecture

Type of order	Toggle
Type of case	Fixed built-in
Number of poles	3 P
Type of pole	3P3D

### Functions

Complete device with protection unit	yes
Trip Unit	TM F/F
Integrated earth fault protection	no

### Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

### Controls and indicators

Motor drive integrated	no
------------------------	----

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	220/415 V

### Voltage

Rated insulation voltage	690 V
Rated impulse withstand voltage	8000 V
With under voltage release	no

### Electric current

Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	40 kA
Rated service breaking capacity Ics AC according IEC 60947-2	50 %
Breaking capacity on 1 pole with 230 V NF 60947-2	51 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	9 kA
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2	85 kA

Technical Properties

Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 415V AC IEC 60947-2	40 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 440V AC IEC 60947-2	25 kA
Rated ultimate short-circuit breaking capacity I <sub>cu</sub> under 690V AC IEC 60947-2	6 kA
Thermal protection nob setting xIN	1

**Current correction factors**

Correction factor of rating current for 2 devices placed 1 side-by-side	
Correction factor of rating current for 3 devices placed 1 side-by-side	
Correction factor of rating current for 4 and 5 devices 1 placed side-by-side	1
Correction factor of rating current for 6 devices placed 1 side-by-side	

**Power**

Power loss per pole at I <sub>n</sub>	4,6 W
Total power loss under I <sub>N</sub>	13,7 W

**Tripping**

Trip mode	TM
Time of response when opening	10 ms

**Endurance**

Electric endurance in number of cycles	1000
Number of mechanical operations	4000

**Installation, mounting**

Tightening torque	6Nm
DIN rail mounting with optional adaptor	yes

**Connection**

Connection cross-sect. rigid cable	4 / 95mm <sup>2</sup>
Connection cross-sect. flexible conductor	4 / 70mm <sup>2</sup>
Connection	Front connection
Type of connection	with screw

**Settings**

Setting type I <sub>n</sub> or I <sub>th</sub>	IN
Range of the magnetic adjustment	600 A

**Equipment**

Motor drive optional	no
----------------------	----

**Use cases**

Category of use	A
-----------------	---

**Standards**

Standard text	IEC 60947-2
European directive WEEE	not concerned

**Safety**

Protection index IP	IP4X
---------------------	------

**Use conditions**

Altitude	2000 m
Storage temperature	-35 to 70 °C
Air humidity protection	for all climates