

MCCB X250 3P 40kA 200A TM

Architecture

Type of order	Toggle
Type of case	Fixed built-in
Number of poles	3 P
Type of pole	3P3D

Functions

Complete device with protection unit	yes
Trip Unit	TM A/A
Integrated earth fault protection	no

Compatibility

Compatible with DIN rail mounting	no
-----------------------------------	----

Controls and indicators

Motor drive integrated	no
------------------------	----

Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	220/415 V

Voltage

Rated insulation voltage	800 V
Rated impulse withstand voltage	8000 V
With under voltage release	no

Electric current

Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2	40 kA
Rated service breaking capacity Ics AC according IEC 60947-2	50 %
Breaking capacity on 1 pole with 230 V NF 60947-2	51 kA
Breaking capacity on 1 pole with 400 V NF 60947-2	9 kA
Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2	85 kA
Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2	40 kA
Rated ultimate short-circuit breaking capacity Icu under 440V AC IEC 60947-2	30 kA
Rated ultimate short-circuit breaking capacity Icu under 690V AC IEC 60947-2	4 kA
Thermal protection nob setting xIN	0,63/0,8/1

Current correction factors

Correction factor of rating current for 2 devices placed 1 side-by-side

Correction factor of rating current for 3 devices placed 1 side-by-side

Correction factor of rating current for 4 and 5 devices 1 placed side-by-side

Correction factor of rating current for 6 devices placed 1 side-by-side

Power

Power loss per pole at I_n 8,3 W

Power loss per pole at $0.63 \cdot I_n$ 3,2 W

Power loss per pole at $0.8 \cdot I_n$ 5,3 W

Total power loss under I_n 24,8 W

Total power loss at $0.63 \cdot I_n$ 9,7 W

Total power loss at $0.8 \cdot I_n$ 15,9 W

Tripping

Trip mode TM

Time of response when opening 10 ms

Endurance

Electric endurance in number of cycles 1000

Number of mechanical operations 4000

Installation, mounting

Tightening torque 12Nm

DIN rail mounting with optional adaptor yes

Connection

Connection cross-sect. rigid cable 35 / 185mm²

Connection cross-sect. flexible conductor 35 / 150mm²

Connection Front connection

Type of connection Terminal

Settings

Magnetic protection nob setting xI_n 6/8/10/13

Setting type I_n or I_{th} I_n

Range of the magnetic adjustment 1200/1600/2000/2600 A

Equipment

Motor drive optional yes

Use cases

Category of use A

Standards

Standard text IEC 60947-2

European directive WEEE not concerned

Safety

Protection index IP	IP4X
---------------------	------

Use conditions

Altitude	2000 m
Storage temperature	-35 to 70 °C
Air humidity protection	for all climates
