



MCCB h630 3P 50kA 400A LSI

HND400H

Architecture

| | |
|-----------------|----------------|
| Type of order | Toggle |
| Type of case | Fixed built-in |
| Number of poles | 3 P |
| Type of pole | 3P3D |

Functions

| | |
|--------------------------------------|-----|
| Complete device with protection unit | yes |
| Trip Unit | LSI |
| Integrated earth fault protection | no |

Compatibility

| | |
|-----------------------------------|----|
| Compatible with DIN rail mounting | no |
|-----------------------------------|----|

Controls and indicators

| | |
|------------------------|----|
| Motor drive integrated | no |
|------------------------|----|

Main electrical features

| | |
|------------------------------|-----------|
| Frequency | 50/60 Hz |
| Rated operational voltage Ue | 220/690 V |

Voltage

| | |
|---------------------------------|--------|
| Rated insulation voltage | 800 V |
| Rated impulse withstand voltage | 8000 V |
| With under voltage release | no |

Electric current

| | |
|------------------------------------------------------------------------------|-------|
| Rated ultimate short-circuit breaking capacity Icu under 400V AC IEC 60947-2 | 50 kA |
| Rated service breaking capacity Ics AC according IEC 60947-2 | 100 % |
| Breaking capacity on 1 pole with 230 V NF 60947-2 | 51 kA |
| Breaking capacity on 1 pole with 400 V NF 60947-2 | 9 kA |
| Rated ultimate short-circuit breaking capacity Icu under 230V AC IEC 60947-2 | 85 kA |
| Rated ultimate short-circuit breaking capacity Icu under 240V AC IEC 60947-2 | 85 kA |

Technical Properties

| | |
|------------------------------------------------------------------------------|-----------------------------|
| Rated ultimate short-circuit breaking capacity Icu under 415V AC IEC 60947-2 | 50 kA |
| Rated ultimate short-circuit breaking capacity Icu under 440V AC IEC 60947-2 | 45 kA |
| Rated ultimate short-circuit breaking capacity Icu under 690V AC IEC 60947-2 | 20 kA |
| Thermal protection nob setting xIN | 0,4/0,5/0,63/0,8/0,9/0,95/1 |

Current correction factors

| | |
|-------------------------------------------------------------------------------|--|
| Correction factor of rating current for 2 devices placed 1 side-by-side | |
| Correction factor of rating current for 3 devices placed 1 side-by-side | |
| Correction factor of rating current for 4 and 5 devices 1 placed side-by-side | |
| Correction factor of rating current for 6 devices placed 1 side-by-side | |

Power

| | |
|--------------------------------------------|--------|
| Power loss per pole at I _n | 20,8 W |
| Power loss per pole at 0.63*I _n | 8,3 W |
| Power loss per pole at 0.8*I _n | 13,3 W |
| Total power loss under I _N | 62,4 W |
| Total power loss at 0.63*I _n | 24,8 W |
| Total power loss at 0.8*I _n | 39,9 W |

Tripping

| | |
|-------------------------------|---------------------|
| Trip mode | LSI |
| Thermal protection trip time | 5/10/11/19/21/29 ms |
| Time of response when opening | 10 ms |

Electrical specifications

| | |
|--------------------------|---------------|
| Magnetic trip delay time | 100 to 200 ms |
|--------------------------|---------------|

Endurance

| | |
|----------------------------------------|------|
| Electric endurance in number of cycles | 1000 |
| Number of mechanical operations | 4000 |

Installation, mounting

| | |
|-------------------------------------------|------|
| Tightening torque | 22Nm |
| DIN rail mounting with optional adaptator | no |

Connection

| | |
|-------------------------------------------|-------------------------|
| Connection cross-sect. rigid cable | 35 / 240mm ² |
| Connection cross-sect. flexible conductor | 35 / 240mm ² |
| Connection | Front connection |
| Type of connection | Terminal |

Settings

| | |
|------------------------------------------------|--------------------------------------|
| Magnetic protection nob setting xIN | 2,5/5/10 |
| Setting type I _n or I _{th} | I _r Th |
| Range of the magnetic adjustment | 2240/2800/3500/4480/5040/5200/5200 A |

Equipment

| | |
|----------------------|-----|
| Motor drive optional | yes |
|----------------------|-----|

Use cases

| | |
|-----------------|---|
| Category of use | A |
|-----------------|---|

Standards

| | |
|-------------------------|-------------|
| Standard text | IEC 60947-2 |
| European directive WEEE | concerned |

Safety

| | |
|---------------------|------|
| Protection index IP | IP4X |
|---------------------|------|

Use conditions

| | |
|-------------------------|------------------|
| Altitude | 2000 m |
| Storage temperature | -35 to 70 °C |
| Air humidity protection | for all climates |