



LS503

## Fuse carrier 3P 32A L38 3M

### Architecture

Type of pole	3 P
--------------	-----

### Controls and indicators

Indicator lamp	no
----------------	----

### Connectivity

Top connection alignment for modular devices	Aligned terminal
--	------------------

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	690 V

### Voltage

Rated insulation voltage	690 V
--------------------------	-------

### Electric current

Rating current of fuse cartridge	2/4/6/8/10/12/16/20/25/32 A
----------------------------------	-----------------------------

### Fuse

CharactFuse	gG
Fuse Size	10.3 x 38

### Power

Power loss per pole at In	0,69 W
Total power loss under IN	11,1 W

### Endurance

Number of mechanical operations	4000
---------------------------------	------

**Dimensions**

Depth of installed product	75 mm
Height of installed product	83 mm
Width of installed product	54 mm

**Installation, mounting**

Tightening torque	2,2Nm
-------------------	-------

**Connection**

Connection cross-sect. rigid cable	1 / 25mm <sup>2</sup>
Connection cross-sect. flexible conductor	0,75 / 16mm <sup>2</sup>

**Standards**

European directive WEEE	concerned
-------------------------	-----------

**Safety**

Protection index IP	IP20
---------------------	------

**Use conditions**

Degree of pollution according to IEC 60664 / IEC 60947-2	3
Storage temperature	-25 to 80 °C

**temperatur**

Temperature of calibration	30 °C
----------------------------	-------