



## Latching relay 2NO 24V

EPN524

### Main electrical features

Frequency	50/60 Hz
Rated operational voltage Ue	250 V

### Voltage

Rated insulation voltage	250 V
Command voltage AC	24 V
DC control voltage	12 V

### Electric current

Quiescent current	6 mA
Rating	16 A

### Power

Inrush power absorbed	25 VA
Total power loss under IN	2,4 W

### Resistance

Winding resistance	12,8 ?
--------------------	--------

### Endurance

Electrical durability at nominal load in AC21 in operating cycles	150000
Number of mechanical operations	500000

### Dimensions

Depth of installed product	63 mm
Height of installed product	83 mm
Width of installed product	17,5 mm

### Installation, mounting

Tightening torque	1,6Nm
-------------------	-------

#### Connection

Connection cross-sect. rigid cable	1,5 / 10mm <sup>2</sup>
Connection cross-sect. flexible conductor	1 / 6mm <sup>2</sup>
Type of connection	with screw
Number of contacts	2
Type of contacts	2NO

#### Equipment

Type of latching relay	electromechanic
------------------------	-----------------

#### Use

Pulse duration	50 ms
----------------	-------

#### Standards

European directive WEEE	concerned
-------------------------	-----------

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Storage temperature	-40 to 80 °C
---------------------	--------------

#### Identification

Device family	EP
---------------	----