



slottet panel trunking HA7 80x40, lg

HA780040

#### Architecture

|          |    |
|----------|----|
| Flexible | no |
|----------|----|

#### Configuration

|                         |         |
|-------------------------|---------|
| Side wall configuration | Slotted |
|-------------------------|---------|

#### Electric current

|                     |     |
|---------------------|-----|
| Current leak stable | yes |
|---------------------|-----|

#### Cover, door

|           |       |
|-----------|-------|
| Lid shape | loose |
|-----------|-------|

#### Materials

|                           |                       |
|---------------------------|-----------------------|
| RAL colour                | RAL 7035 - Light grey |
| Colour                    | light grey            |
| Material                  | PC-ABS                |
| Type of surface treatment | untreated             |

#### Dimensions

|                 |         |
|-----------------|---------|
| Length          | 2000 mm |
| Trunking height | 80 mm   |
| Trunking width  | 40 mm   |
| Slot width      | 6 mm    |
| Tongue width    | 6,5 mm  |

#### Installation, mounting

|             |                 |
|-------------|-----------------|
| Fixing type | bottom punching |
|-------------|-----------------|

#### Cable

|  |                      |
|--|----------------------|
| Number of wires 1,5 mm <sup>2</sup> - 40% filling degree | 97                   |
| Number of wires 2,5 mm <sup>2</sup> - 40% filling degree | 69                   |
| Number of wires 1,0 mm <sup>2</sup> - 40% filling degree | 135                  |
| Internal/useful cross section                            | 2498 mm <sup>2</sup> |

**Standards**

|                         |                      |
|-------------------------|----------------------|
| Approvals               | EN50085-2-3          |
| European directive RoHs | voluntary compliance |
| UL 94 classification    | V0                   |

**Safety**

|                          |     |
|--------------------------|-----|
| Halogen free             | yes |
| Fireproof classification | M1  |

**Use conditions**

|  |           |
|--|-----------|
| Ambient temperature (operation temprature) | -25/90 °C |
|--|-----------|