



Systo 1M PB 10+1F w. light

WS030



Architecture

| | |
|---------------|-------------|
| Type of order | push button |
| Fixing mode | Recessed |

Controls and indicators

| | |
|----------------|-----------------|
| Indicator lamp | as an accessory |
|----------------|-----------------|

Main electrical features

| | |
|-----------------|----------|
| Frequency | 50/60 Hz |
| Nominal voltage | 250 V |

Materials

| | |
|---------------------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
| Colour | white |
| Material | Polycarbonate (PC) |
| Type of surface treatment | mat |

Dimensions

| | |
|-----------------------------|------------|
| Depth of installed product | 33 mm |
| Height of installed product | 45 mm |
| Width of installed product | 22 mm |
| Dimensions (LLxwxhh) | 22.5x45x33 |

Installation, mounting

| | |
|-------------|---------|
| Fixing type | Clipped |
|-------------|---------|

Connection

| | |
|--------------------|---------------|
| Type of connection | quick connect |
| Type of contacts | 1NC+1NO |

Standards

| | |
|-----------|------------|
| Approvals | EN 60669-1 |
|-----------|------------|

Safety

| | |
|---|--------------------------------|
| Protection index IP | IP31D |
| IK protection code against mechanical impacts | 07 |
| Glow wire test | according to NFC-20455 : 960°C |

Use conditions

| | |
|---------------------|--------------|
| Storage temperature | -10 to 50 °C |
|---------------------|--------------|

Identification

| | |
|-------|-------|
| Range | systo |
|-------|-------|