Product data sheet WS160V





Systo Socket Schuko screwless Green

WS160V



Type of pole	SCHUKO
Fixing mode	universal fixing
Functions	
Overvoltage protection	no
Controls and indicators	
Indicator lamp	no
Main electrical features	
Frequency	50/60 Hz
Nominal voltage	250 V
Cover, door	
Interlockable	no
Interlockable	no
Interlockable Materials	no RAL 6029 - Mint green
Interlockable Materials RAL colour Material	
Interlockable Materials RAL colour Material Surface appearance	RAL 6029 - Mint green
Interlockable Materials RAL colour Material	RAL 6029 - Mint green Polycarbonate (PC)
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment	RAL 6029 - Mint green Polycarbonate (PC) matt
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product	RAL 6029 - Mint green Polycarbonate (PC) matt
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product	RAL 6029 - Mint green Polycarbonate (PC) matt Painted
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product Height of installed product Length	RAL 6029 - Mint green Polycarbonate (PC) matt Painted 22,8 mm
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product Height of installed product Length Width of installed product	RAL 6029 - Mint green Polycarbonate (PC) matt Painted 22,8 mm 40 mm 45 mm 45 mm
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product Height of installed product Length	RAL 6029 - Mint green Polycarbonate (PC) matt Painted 22,8 mm 40 mm 45 mm
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product Height of installed product Length Width of installed product	RAL 6029 - Mint green Polycarbonate (PC) matt Painted 22,8 mm 40 mm 45 mm 45 mm
Interlockable Materials RAL colour Material Surface appearance Type of surface treatment Dimensions Depth of installed product Height of installed product Length Width of installed product Dimensions (LLxwwxhh)	RAL 6029 - Mint green Polycarbonate (PC) matt Painted 22,8 mm 40 mm 45 mm 45 mm

Architecture

Connection

Connection cross-sect. rigid cable	1,5 / 2,5mm²
Type of connection	quick connect
Equipment	
On/Off switch	no
Standards	
Approvals	VDE
Safety	
Protection index IP	IP2X
IK protection code against mecanical impacts	07
Halogen free	yes
Identification	
Range	systo