

Systo 2M local control for shutter

WS304

Fixing mode	flush-mounting
Main electrical features	
Nominal voltage	230 V
Materials	
RAL colour	RAL 9010 - Pure white
Material	Polycarbonate (PC)
Surface appearance	satin finish
Type of surface treatment	Painted
Dimensions	
Width of installed product	73 mm
Width of installed product Dimensions (LLxwwxhh)	73 mm 71x3x71
Dimensions (LLxwwxhh)	
Dimensions (LLxwwxhh) Installation, mounting Fixing type	71x3x71
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection	71x3x71
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection Connection cross-sect. rigid cable	71x3x71 With screws or claws
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection Connection cross-sect. rigid cable Connection cross-sect. flexible conductor Type of connection	71x3x71 With screws or claws 0,08 / 2,5mm²
Dimensions (LLxwwxhh) Installation, mounting	71x3x71 With screws or claws 0,08 / 2,5mm ² 0,2 / 2,5mm ²
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection Connection cross-sect. rigid cable Connection cross-sect. flexible conductor Type of connection	71x3x71 With screws or claws 0,08 / 2,5mm ² 0,2 / 2,5mm ² with screw
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection Connection cross-sect. rigid cable Connection cross-sect. flexible conductor Type of connection Type of contacts Safety Protection index IP	71x3x71 With screws or claws 0,08 / 2,5mm ² 0,2 / 2,5mm ² with screw
Dimensions (LLxwwxhh) Installation, mounting Fixing type Connection Connection cross-sect. rigid cable Connection cross-sect. flexible conductor Type of connection Type of contacts Safety	71x3x71 With screws or claws 0,08 / 2,5mm² 0,2 / 2,5mm² with screw 2 changeovers

systo

Range