



FERNBEDIENUNG IR

2770

Battery

- with enclosed lithium cell battery 3 V type: CR 2025

Materials

Colour independent of design lines	light grey/dark grey
Colour	light grey
Material	thermoplastic

Dimensions

Height	85 mm
Length	85 mm
Width	52 mm

Settings

- key functions for 2 h ON/OFF, continuous ON/OFF and automatic mode
- key functions for presence simulation, hotel and outdoor mode
- Key function for switch-off advance warning
- Key function for test mode
- with teach function for response brightness
- with 31 function buttons
- key functions for response sensitivity 25%, 50%, 75% and 100%
- Key function for setting minimum brightness (only for operation with dimmer insert)
- Test functions for sensor setting (left, right, both sensors active)
- key functions for setting the delay time: 30 s, 2/5/30 min and individual follow-up time

Identification

Application, usage	Motion detector
Main design line	Motion detectors

Instructions

---

Technical Properties

- Functions and settings for BLC controller master station: 2 h on/off, continuous on/off, dimming (with BLC dimmer insert), short-time, hotel and test mode, switch insert switch-off advance warning, response brightness stages, response brightness continuously learnable, switch-on brightness level storable (for BLC dimmer insert), response sensitivity in stages, delay time in stages and continuously learnable, sensor switch-off for angle of detection limitation, simultaneous operation, reset.

Functions and settings for BLC controller extension unit: extension unit 2 h or continuous OFF, response sensitivity in stages, sensor switch-off for angle of detection limitation, motion LED, reset.

---