

Q.x, PB - cover 2G, for PB-module, pw

80960329

Architecture

Fixing mode

flush-mounting

Functions

- Function for manual interruption of automatic functions already triggered
- operating surfaces as buttons (single-surface operation) and rockers (two-surface operation)
- the brightness of status LEDs are individually adjustable for button/ rocker function
- brightness value of the status LEDs for day/nighttime operation adjustable via object or manually
- value transmitter for dimming, position, brightness temperature values 1 and 2 byte
- integrated temperature sensor with output of the measured values via object
- parameter defineable lock function
- button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation

Controls and indicators

- operating areas configurable as one or two-area operation
- with programming button and red programming LED

Voltage

Operating voltage over bus

21 32 V DC

Camera

- with 2 clear lenses for the RGB status display of the push-button module

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	velvety
Type of surface treatment	Painted

Dimensions

Height 58 mm		
	Height	58 mm

Connection

- with integral bus coupling unit

- bus connection via connecting terminal

Equipment

- with integrated buzzer for acoustic identification of the device within the system

Use

- with clear lens

Safety

Protection index IP	IP20	
- with dismantling protection		

Use conditions

Operating temperature	-5 45 °C
Storage/transport temperature	-20 70 °C (storage at > 45°C
	reduces the service life)

- integrated temperature sensor with output of the measured values via object

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker Q.1/Q.3
Secondary design line(s)	Berker Q.1, Berker Q.3