



Q.x, PB - cover 2G, for PB-module, anth

80960326

#### Architecture

|             |                |
|-------------|----------------|
| Fixing mode | flush-mounting |
|-------------|----------------|

#### Functions

- Function for manual interruption of automatic functions already triggered
- operating surfaces as buttons (single-surface operation) and rockers (two-surface operation)
- the brightness of status LEDs are individually adjustable for button/ rocker function
- brightness value of the status LEDs for day/nighttime operation adjustable via object or manually
- value transmitter for dimming, position, brightness temperature values 1 and 2 byte
- integrated temperature sensor with output of the measured values via object
- parameter defineable lock function
- button/rocker functions for switching, dimming, roller shutter/blind, value transmitter 1/2 byte, room thermostat extension unit, priority, scene, automatic control deactivation

#### Controls and indicators

- operating areas configurable as one or two-area operation
- with programming button and red programming LED

#### Voltage

|                            |            |
|----------------------------|------------|
| Operating voltage over bus | 21 32 V DC |
|----------------------------|------------|

#### Camera

- with 2 clear lenses for the RGB status display of the push-button module

#### Materials

|                           |                       |
|---------------------------|-----------------------|
| RAL colour                | RAL 7021 - Black grey |
| Colour of design line     | anthracite            |
| Material / workmanship    | lacquered             |
| Material                  | thermoplastic         |
| Surface appearance        | velvety               |
| Type of surface treatment | Painted               |

#### Dimensions

|        |       |
|--------|-------|
| Height | 58 mm |
|--------|-------|

#### Connection

- with integral bus coupling unit
- bus connection via connecting terminal

#### Equipment

- with integrated buzzer for acoustic identification of the device within the system

#### Use

- with clear lens

#### Safety

|                               |      |
|-------------------------------|------|
| Protection index IP           | IP20 |
| - with dismantling protection |      |

#### Use conditions

|                                                                               |                                                        |
|-------------------------------------------------------------------------------|--------------------------------------------------------|
| Operating temperature                                                         | -5 45 °C                                               |
| Storage/transport temperature                                                 | -20 70 °C (storage at > 45°C reduces the service life) |
| - integrated temperature sensor with output of the measured values via object |                                                        |

#### Identification

|                          |                             |
|--------------------------|-----------------------------|
| Application, usage       | KNX - operating systems     |
| Product family           | product family: push-button |
| Main design line         | KNX - Berker Q.1/Q.3        |
| Secondary design line(s) | Berker Q.1, Berker Q.3      |