



TOUCHSENSOR 2F M BA GLAS R.1 P-W

75142860

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

- for switch, push-button, dimmer and shutter functions
- Blocking function for sensor surface e.g. for cleaning the glass surface

Compatibility

- extension unit for light scene push-button

Controls and indicators

- operation by gently touching the sensor surfaces on the white LED

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	glass polar white
Colour	white
Material	glass
Surface appearance	glossy
Type of surface treatment	Painted

Dimensions

Depth	23 mm
Height	152 mm
Width	81 mm

LED control

- with blue operation LED and 4 white status LEDs

Installation, mounting

- for vertical mounting

Connection

- with integral bus coupling unit
- bus connection via connecting terminal

Use

- with integral bus coupling unit

Safety

Protection index IP	IP20
Halogen free	no

Use conditions

Operating temperature	-5 45 °C
-----------------------	----------

- temperature measurement via internal temperature sensor or external communication object
- integrated temperature sensor for operation as controller extension unit
- additional connection for external temperature sensor

Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker R.1
Secondary design line(s)	KNX, Berker R.1
