



75144329

Pushbutton 4gang comfort with BCU

Architecture

Fixing mode flush-mounting

Functions

- for switch, push-button, dimmer and shutter functions
- retrieval, adjustment and storage of 8 light scenes

Compatibility

- extension unit for light scene push-button

Controls and indicators

- one push-button operation for switching, pushing, shutters and dimming

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	polarwhite
Material	Plastic/metal
Surface appearance	velvety
Type of surface treatment	untreated

Dimensions

Height	71 mm
Width	71 mm

LED control

- with white operation LED and 8 amber status LEDs

Settings

- single and two push-button operation parameterisable

Equipment

Product type: product type: push-button 4gang

Use

- with labelling fields
- with integral bus coupling unit

Safety

Protection index IP IP20

Halogen free no

- with dismantling protection

Use conditions

Operating temperature -5 45 °C

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Main design line KNX - Berker Q.1/Q.3

Secondary design line(s) Berker Q.3, Berker Q.7, Berker Q.1

Instructions

- Labelling field sheet, order no. 9498 32 04, available separately.
