



## Push-button, 1-gang comfort, with label

75161770

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

- for switch, push-button, dimmer and shutter functions

### Compatibility

- extension unit for light scene push-button

### Controls and indicators

- one push-button operation for switching, pushing, shutters and dimming
- activation of second user level via object

### Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour independent of design lines	polar white
Colour	polarwhite
Material	thermoplastic
Surface appearance	glossy
Type of surface treatment	untreated

### Dimensions

Height	52,8 mm
Width	66,8 mm

#### LED control

- with white operation LED and 2 red status LEDs

#### Connection

- for bus coupling unit flush-mounted

#### Settings

- single and two push-button operation parameterisable

#### Equipment

Product type: product type: push-button 1gang

#### Use

- with labelling field
- with horizontal operation

#### Safety

Protection index IP IP20  
Halogen free no

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

#### Use conditions

Operating temperature -5 45 °C

#### Identification

Application, usage KNX - operating systems  
Product family product family: push-button  
Main design line KNX - Berker K.1  
Secondary design line(s) Berker K.1, KNX