



## TOUCHSENSOR 4F M BA GLAS R3 P-W

75144850

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

- for switch, push-button, dimmer and shutter functions
- Blocking function for sensor surface e.g. for cleaning the glass surface

### Compatibility

- extension unit for light scene push-button

### Controls and indicators

- operation by gently touching the sensor surfaces on the white LED

### Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

### Materials

RAL colour	RAL 9010 - Pure white
Colour of design line	glass polar white
Colour	polarwhite
Material	glass
Surface appearance	glossy
Type of surface treatment	Tampography

### Dimensions

Depth	23 mm
Height	152 mm
Width	81 mm

#### LED control

- with blue operation LED and 8 white status LEDs

#### Installation, mounting

- for vertical mounting

#### Connection

- with integral bus coupling unit
- bus connection via connecting terminal

#### Use

- with integral bus coupling unit

#### Safety

Protection index IP	IP20
Halogen free	no

#### Use conditions

Operating temperature	-5 45 °C
- temperature measurement via internal temperature sensor or external communication object	
- integrated temperature sensor for operation as controller extension unit	
- additional connection for external temperature sensor	

#### Identification

Application, usage	KNX - operating systems
Main design line	KNX - Berker R.3
Secondary design line(s)	KNX, Berker R.3