



TXA111

Power supply 30V DC 320 mA

Architecture

| | |
|-------------|----------|
| Bus system | EIB |
| Fixing mode | Din-Rail |

Main electrical features

| | |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

Power

| | |
|---------------------------|------|
| Total power loss under IN | 15 W |
|---------------------------|------|

Materials

| | |
|------------|-----------------------|
| RAL colour | RAL 7035 - Light grey |
| Colour | stone grey |

Dimensions

| | |
|-----------------------------|-------|
| Depth of installed product | 64 mm |
| Height of installed product | 90 mm |
| Length | 64 mm |
| Width of installed product | 72 mm |

Connection

| | |
|---|---------------------------|
| Conductor cross-section (flexible) | 0,75 2,5 mm ² |
| Conductor cross-section (rigid) | 0,75 2,5 mm ² |
| Connection cross-sect. rigid cable | 0,75 / 2,5mm ² |
| Connection cross-sect. flexible conductor | 0,75 / 2,5mm ² |
| Type of connection | quick connect |

Use

- with labelling field

Safety

| | |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

Use conditions

| | |
|-----------------------|--------------|
| Operating temperature | -5 to 45 °C |
| Storage temperature | -20 to 70 °C |