



Power supply 1x 30V DC + 1x 24V DC

TXA114

#### Architecture

|             |          |
|-------------|----------|
| Bus system  | EIB      |
| Fixing mode | Din-Rail |

#### Connectivity

- one output 30 V DC, 320 mA incl. choke
- one output 24 V, 640 mA

#### Main electrical features

|           |          |
|-----------|----------|
| Frequency | 50/60 Hz |
|-----------|----------|

#### Fuse

- with electronic short-circuit and overload protection

#### Power

|                           |       |
|---------------------------|-------|
| Total power loss under IN | 4,4 W |
|---------------------------|-------|

#### Materials

|            |                       |
|------------|-----------------------|
| RAL colour | RAL 7035 - Light grey |
|------------|-----------------------|

#### Dimensions

|                                    |           |
|------------------------------------|-----------|
| Depth of installed product         | 64 mm     |
| Height of installed product        | 90 mm     |
| Length                             | 64 mm     |
| Width of installed product         | 72 mm     |
| Width of rail mounted device (RMD) | 4 modules |

#### LED control

- with green LED for display of power supply per output
- with red LED for display of short-circuit and overload protection per output

#### Connection

|   |                           |
|---|---------------------------|
| Conductor cross-section (flexible)        | 0,75 2,5 mm <sup>2</sup>  |
| Conductor cross-section (rigid)           | 0,75 2,5 mm <sup>2</sup>  |
| Connection cross-sect. rigid cable        | 0,75 / 2.5mm <sup>2</sup> |
| Connection cross-sect. flexible conductor | 0,75 / 2,5mm <sup>2</sup> |

- protected earth conductor must be connected
- with QuickConnect plug-in terminals

#### Use

- with labelling field

#### Safety

|                     |      |
|---------------------|------|
| Protection index IP | IP20 |
|---------------------|------|

#### Use conditions

|                       |              |
|-----------------------|--------------|
| Operating temperature | -5 45 °C     |
| Storage temperature   | -20 to 70 °C |