



Power supply 2x 30V DC 640 mA

TXA116

Architecture

Bus system	EIB
Fixing mode	Din-Rail

Connectivity

- with 2 outputs incl. choke per output

Main electrical features

Frequency	50/60 Hz
-----------	----------

Fuse

- with electronic short-circuit and overload protection

Power

Total power loss under IN	3,5 W
---------------------------	-------

Materials

RAL colour	RAL 7035 - Light grey
------------	-----------------------

Dimensions

Depth of installed product	64 mm
Height of installed product	90 mm
Length	64 mm
Width of installed product	72 mm
Width of rail mounted device (RMD)	4 modules

LED control

- with green LED for display of power supply per output
- with red LED for display of short-circuit and overload protection per output

Connection

Conductor cross-section (flexible)	0,75 2,5 mm ²
Conductor cross-section (rigid)	0,75 2,5 mm ²
Connection cross-sect. rigid cable	0,75 / 2,5mm ²
Connection cross-sect. flexible conductor	0,75 / 2,5mm ²

- protected earth conductor must be connected
- with QuickConnect plug-in terminals

Use

- with labelling field

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5 45 °C
Storage temperature	-20 to 70 °C