



## Output 4 -fold 16A

TXA204C

### Architecture

Bus system	EIB
Fixing mode	Din-Rail

### Functions

- suitable to switch different external conductors

### Controls and indicators

Indicator lamp	yes
----------------	-----

### Main electrical features

Rated current	16 A
Rated operational voltage Ue	207/230/264 V

### Voltage

Operating voltage over bus	21 32 V DC
----------------------------	------------

### Power

Total power loss under IN	3 W
---------------------------	-----

### Materials

Colour	stone grey
--------	------------

### Fluorescent bulbs control

Max. power fluo. duo lamp comp. series	20 x 36 W
--	-----------

### Incandescent bulbs control

Max. power with incandescent lamps	2300 W
------------------------------------	--------

**Connection**

---

Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
------------------------------------	---------------------------

---

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
---	---------------------------

---

Type of connection	quick connect
--------------------	---------------

---

Type of contacts	4NO
------------------	-----

---

- with integral bus coupling unit

- bus connection via connecting terminal

---

**Safety**

---

Protection index IP	IP20
---------------------	------

---

**Use conditions**

---

Storage temperature	-20 to 70 °C
---------------------	--------------

---

Storage/transport temperature	-20 70 °C
-------------------------------	-----------

---

**Identification**

---

Main design line	KNX
------------------	-----

---