



TXA206A

## Output 6 -fold 4A

### Architecture

Bus system	EIB
Fixing mode	Din-Rail

### Functions

- suitable to switch different external conductors

### Controls and indicators

Indicator lamp	yes
----------------	-----

### Main electrical features

Rated current	4 A
Rated operational voltage Ue	230 V

### Voltage

Operating voltage over bus	21 - 32 V DC
----------------------------	--------------

### Power

Total power loss under IN	1 W
---------------------------	-----

### Materials

Colour	stone grey
--------	------------

### Fluorescent bulbs control

Max. power fluo. duo lamp comp. series	12 x 36 W
----------------------------------------	-----------

### Incandescent bulbs control

Max. power with incandescent lamps	800 W
------------------------------------	-------

#### Connection

Connection cross-sect. rigid cable	0,75 / 2.5mm <sup>2</sup>
------------------------------------	---------------------------

Connection cross-sect. flexible conductor	0,75 / 2,5mm <sup>2</sup>
-------------------------------------------	---------------------------

Type of connection	quick connect
--------------------	---------------

Type of contacts	6NO
------------------	-----

- with integral bus coupling unit

- bus connection via connecting terminal

#### Safety

Protection index IP	IP20
---------------------	------

#### Use conditions

Storage temperature	-20 to 70 °C
---------------------	--------------

Storage/transport temperature	-20 70 °C
-------------------------------	-----------

#### Identification

Main design line	KNX
------------------	-----