## Output 10 -fold 16A

TXA207C

### Architecture

| | |
|---|---|
| Bus system | EIB |
| Fixing mode | Din-Rail |

### Functions

- suitable to switch different external conductors

### Controls and indicators

| | |
|---|---|
| Indicator lamp | yes |

### Main electrical features

| | |
|---|---|
| Rated current | 16 A |
| Rated operational voltage Ue | 230 V |

### Voltage

| | |
|---|---|
| Operating voltage over bus | 21 32 V DC |

### Power

| | |
|---|---|
| Total power loss under IN | 15 W |

### Materials

| | |
|---|---|
| Colour | stone grey |

### Fluorescent bulbs control

| | |
|---|---|
| Max. power fluo. duo lamp comp. series | 20 x 36 W |

### Incandescent bulbs control

| | |
|---|---|
| Max. power with incandescent lamps | 2300 W |

### Connection

| | |
|---|---|
| Connection cross-sect. rigid cable | 0,75 / 2.5mm² |
| Connection cross-sect. flexible conductor | 0,75 / 2,5mm² |
| Type of connection | quick connect |
| Type of contacts | 10NO |
| - with integral bus coupling unit<br>- bus connection via connecting terminal | |

### Safety

| | |
|---|---|
| Protection index IP | IP20 |

### Use conditions

| | |
|---|---|
| Storage temperature | -20 to 70 °C |
| Storage/transport temperature | -20 70 °C |

### Identification

| | |
|---|---|
| Main design line | KNX |