



TXA023

Weekly time switch 2 channels with DCF

Architecture

Bus system	EIB
Fixing mode	Din-Rail

Functions

- DCF compatible via radio antenna
- Functions e.g. switching, dimming, blinds, light scenes, heating, operating modes, date, time

Controls and indicators

- with 5 manual operation buttons
- LCD display for commissioning

Voltage

Operating voltage over bus	21 32 V DC
----------------------------	------------

Power

Total power loss under IN	0,3 W
Dissipated energy in cable	1 W

Battery

Lithium cell power reserve [years]	~ 5
------------------------------------	-----

Materials

RAL colour	RAL 7035 - Light grey
------------	-----------------------

Dimensions

Depth of installed product	97 mm
Height of installed product	85 mm
Length	97 mm
Width of installed product	36 mm
Width of rail mounted device (RMD)	2 modules

Connection

Conductor cross-section (flexible)	1,5 10 mm ²
Conductor cross-section (rigid)	1 6 mm ²
Type of connection	with screw

- with integral bus coupling unit
- with screw terminals
- bus connection via connecting terminal

Settings

Summer / Winter time change	automatic
Shortest switching time	1 mn
Type of programming	digital

Equipment

Number of program steps	56
Number of channels	2
Supply failure reserve	lithium battery

Use

Cycle	weekly
-------	--------

- with hinged cover
- with display
- with integrated bus coupling unit

Safety

Protection index IP	IP20
---------------------	------

- with programming key

Use conditions

Operating temperature	0 45 °C
Storage temperature	-20 to 70 °C

Identification

Main design line	KNX
------------------	-----