



Push-button, 2-gang comfort, with label

75162775

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

- for switch, push-button, dimmer and shutter functions

Compatibility

- extension unit for light scene push-button

Controls and indicators

- one push-button operation for switching, pushing, shutters and dimming
- activation of second user level via object

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Materials

RAL colour	RAL 7016 - Anthracite grey
Colour of design line	anthracite
Colour	anthracite
Material	thermoplastic
Surface appearance	matt
Type of surface treatment	Painted

Dimensions

Height	52,8 mm
Width	66,8 mm

LED control

- with white operation LED and 4 red status LEDs

Connection

- for bus coupling unit flush-mounted

Settings

- single and two push-button operation parameterisable

Equipment

Product type:	product type: push-button 2gang
---------------	---------------------------------

Use

- with labelling fields
- with horizontal operation

Safety

Protection index IP	IP20
---------------------	------

Halogen free	no
--------------	----

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature	-5 45 °C
-----------------------	----------

Identification

Application, usage	KNX - operating systems
Product family	product family: push-button
Main design line	KNX - Berker K.1
Secondary design line(s)	Berker K.1, KNX