



Push-button, 3-gang comfort, with label

75163773

Architecture

Fixing mode	flush-mounting
-------------	----------------

Functions

- for switch, push-button, dimmer and shutter functions

Compatibility

- extension unit for light scene push-button

Controls and indicators

- one push-button operation for switching, pushing, shutters and dimming
- activation of second user level via object

Measurement

- value transmitter for dimming, position, brightness and temperature values 1 and 2 byte

Materials

RAL colour	RAL 9022 - Pearl light grey
Colour of design line	stainless steel
Colour	stainless steel
Material	thermoplastic
Surface appearance	glossy
Type of surface treatment	untreated

Dimensions

Height	55,1 mm
Width	70,5 mm

LED control

- with white operation LED and 6 red status LEDs

Connection

- for bus coupling unit flush-mounted

Settings

- single and two push-button operation parameterisable

Equipment

Product type: product type: push-button 3gang

Use

- with labelling fields
- with horizontal operation

Safety

Protection index IP IP20

Halogen free no

- with dismantling protection
- alarm telegram after disconnection from bus coupling unit 1 bit or 1 byte

Use conditions

Operating temperature -5 45 °C

Storage/transport temperature -20 70 °C (storage at > 45°C reduces the service life)

Identification

Application, usage KNX - operating systems

Product family product family: push-button

Main design line KNX - Berker K.5

Secondary design line(s) Berker K.5, KNX