



HBNet ZSU JAL K1 ANTH MATT

85741175

Functions

Power reserve	~ 24 h
<ul style="list-style-type: none">- reset function (to factory setting)- with keylock- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)- with switchover manual/automatic mode	

Controls and indicators

<ul style="list-style-type: none">- LC display illuminated during operation- indication of the application module/insert compatibility in the display- LC display contrast is adjustable	
--	--

Power

<ul style="list-style-type: none">- low intrinsic energy requirement	
--	--

Measurement

Relative humidity (without condensation)	0 65 % (without condensation)
--	-------------------------------

Detection

<ul style="list-style-type: none">- Not suitable for rain and wind sensors	
--	--

Materials

Colour of design line	anthracite
Colour	anthracite
Material / workmanship	lacquered
Material	Plastic/metal

Installation, mounting

<ul style="list-style-type: none">- clamp fastening	
---	--

Settings

- with automatic summer-/winter time switching (can be switched off)
- astro programme for sunrise/sundown switching with city/country or co-ordinate input, individually adaptable
- holiday programme for random variation of the operation times in automatic operation

Equipment

- 2 independent preset programme memories, individually adaptable

Use

- with display

Safety

- with dismantling protection

Use conditions

Operating temperature	-5 45 °C
-----------------------	----------

Identification

Application, usage	Blind control
Main design line	Berker K.1

Instructions

- Can be switched to orientation led by extension unit.