



## HBNet ZSU JAL K1 P-W GLÄ

85741179

### Functions

Power reserve	~ 24 h
<ul style="list-style-type: none"> <li>- reset function (to factory setting)</li> <li>- with keylock</li> <li>- Party function, no execution of automatic, radio and extension unit commands (lock-out protection)</li> <li>- with switchover manual/automatic mode</li> </ul>	

### Controls and indicators

<ul style="list-style-type: none"> <li>- LC display illuminated during operation</li> <li>- indication of the application module/insert compatibility in the display</li> <li>- LC display contrast is adjustable</li> </ul>	
--	--

### Power

- low intrinsic energy requirement
------------------------------------

### Measurement

Relative humidity (without condensation)	0 65 % (without condensation)
--	-------------------------------

### Detection

- Not suitable for rain and wind sensors
--

### Materials

Colour of design line	polar white
Colour	polarwhite
Material	Plastic/metal

### Installation, mounting

- clamp fastening
-------------------

#### Settings

- with automatic summer-/winter time switching (can be switched off)
- astro programme for sunrise/sundown switching with city/country or co-ordinate input, individually adaptable
- holiday programme for random variation of the operation times in automatic operation

#### Equipment

- 2 independent preset programme memories, individually adaptable

#### Use

- with display

#### Safety

- with dismantling protection

#### Use conditions

Operating temperature	-5 45 °C
-----------------------	----------

#### Identification

Application, usage	Blind control
Main design line	Berker K.1

#### Instructions

- Can be switched to orientation led by extension unit.