



SKO-STD M AMBEL SRBKL K.X ANTH HGL

41097006

Architecture

Design	according to DIN 49440
--------	------------------------

Main electrical features

Rated current	16 A
Rated voltage	250 V AC

Power

Power consumption	0.25 W/0.35 VA
-------------------	----------------

Cover, door

- Central cover plate

Detection

- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness

Materials

RAL colour	RAL 7021 - Black grey
Colour of design line	anthracite
Colour	anthracite charcoal grey
Colour	anthracite
Material / workmanship	lacquered
Material	thermoplastic
Surface appearance	matt

Dimensions

Insertion depth	32 mm
-----------------	-------

LED control

- white LED light
- long service life of the LED

Installation, mounting

- with spreader claws
-

Connection

Conductor cross-section (rigid)	max. 2,5 mm ²
Connection terminals	according to IEC 60884-1

- with screw-in lift terminals

Cable

- through-wiring possible, therefore also ideal for retrofitting
-

Equipment

- additional benefit by combination of a socket outlet with an orientation light
-

Use

- enhanced contact protection
 - Screw-in lift terminals
-

Safety

Protection index IP	IP20
IK protection code against mechanical impacts	05

- Enhanced contact protection

Identification

Main design line	Berker K.1
------------------	------------

Instructions

- Caution!
Items with special flush-mounted insert.
Centre plates with LED orientation lights are not compatible with the standard socket outlets.
-