



41097009

SKO-STD M AMBEL SRBKL K.X P-W HGL

<b>Architecture</b>	
Design	according to DIN 49440
<b>Main electrical features</b>	
Rated current	16 A
Rated voltage	250 V AC
<b>Power</b>	
Power consumption	0.25 W/0.35 VA
<b>Cover, door</b>	
- Central cover plate	
<b>Detection</b>	
- integrated brightness sensor that switches the orientation light on at twilight and off when there is sufficient brightness	
<b>Materials</b>	
RAL colour	RAL 9010 - Pure white
Colour of design line	polar white
Colour	white
Colour	polarwhite
Material	thermoplastic
Surface appearance	glossy
<b>Dimensions</b>	
Insertion depth	32 mm
<b>LED control</b>	
- white LED light	
- long service life of the LED	

#### Installation, mounting

---

- with spreader claws
- 

#### Connection

---

Conductor cross-section (rigid)	max. 2,5 mm <sup>2</sup>
Connection terminals	according to IEC 60884-1
- with screw-in lift terminals	

---

#### Cable

---

- through-wiring possible, therefore also ideal for retrofitting
- 

#### Equipment

---

- additional benefit by combination of a socket outlet with an orientation light
- 

#### Use

---

- enhanced contact protection
  - with screw-in lift terminals
- 

#### Safety

---

Protection index IP	IP20
IK protection code against mechanical impacts	05
- Enhanced contact protection	

---

#### Identification

---

Main design line	Berker K.1
------------------	------------

---

#### Instructions

---

- Caution!  
Items with special flush-mounted insert.  
Centre plates with LED orientation lights are not compatible with the standard socket outlets.
-