



## HBNet WÄCH STAND 2,2 M K5 E-STAHL

85342173

### Architecture

Fixing mode	flush-mounting
-------------	----------------

### Functions

- $\mu$ -processor controlled mode of operation
- Teach function for response brightness via button
- with keylock
- Party function for switching on for 2 hours
- with memory function for presence simulation

### Controls and indicators

- with button for on/off/automatic

### Power

- low intrinsic energy requirement

### Measurement

Relative humidity (without condensation)	0 65 % (without condensation)
Detection field, rectangular shaped	~ 8 x 12 m

### Reach distance

Range, frontal	~ 8 m
Range, side	each ~ 6 m

### Detection

Number of detection levels	3
Detection angle, settable	each side ~ 45 90 °

### Materials

Colour of design line	stainless steel
Colour	stainless steel
Material / workmanship	lacquered
Material	thermoplastic

#### Dimensions

Assembling height	34 mm
Nominal mounting height	2,2 m

#### Lighting control

Response brightness, adjustable	~ 5 1000 lx , daytime operation
---------------------------------	---------------------------------

#### LED control

- with operation and status LED, red/green/orange
- LED application module/insert compatibility display

#### Settings

Response sensitivity, settable	10 100 %
Switch-off pre-warning to dimming value 50% for	30 s

#### Safety

Protection index IP	IP20
- with dismantling protection	

#### Use conditions

Operating temperature	-5 45 °C
-----------------------	----------

#### Identification

Application, usage	Light control, Motion detector
Secondary design line(s)	Motion detector, Berker K.5