



Hotel card switch electr. K.5 aluminium

16417134

Main electrical features

Rated voltage	230 V AC
---------------	----------

Electric current

Switching current	10 A /230 V AC1
-------------------	-----------------

Power

Power consumption	< 0.2 W
Conventional transformers	1500 VA
Electronic transformers	1500 W

Materials

RAL colour	RAL 9006 - White aluminium
Colour of design line	aluminium
Colour	aluminium optics
Colour	aluminium
Material / workmanship	lacquered
Material	Plastic/metal
Surface appearance	matt

Dimensions

Depth	58,6 mm
Insertion depth	32 mm
Height	71 mm
Width	71 mm

Fluorescent bulbs control

Compact fluorescent lamps	500 W
Fluorescent lamps in duo circuit	1500 W

LED control

- illuminated with blue LED if hotel card is not inserted

Incandescent bulbs control

230 V incandescent lamps and halogen lamps	1500 W
--	--------

Installation, mounting

- with spreader claws

Connection

- with screw-in lift terminals

Settings

- with potentiometer for incremental adjustment of delay time

Equipment

- for illumination
- with potential-free contact

Safety

Protection index IP	IP20
---------------------	------

Use conditions

Operating temperature	-5 ... 50 °C
Storage/transport temperature	-25 ... 70 °C (storage at > 45°C reduces the service life)

Identification

Application, usage	Light control
Main design line	Berker K.5