



SKO STD M KLD U ERHBS R.1 SCHW

47442045

**Architecture**

Design according to DIN 49440

**Main electrical features**

Rated current 16 A  
Rated voltage 250 V AC

**Cover, door**

- with self-closing hinged covers
- Central cover plate

**Materials**

RAL colour RAL 9005 - Jet black  
Colour of design line black  
Colour deep black  
Colour black  
Material thermoplastic  
Surface appearance glossy

**Installation, mounting**

- mounting orientation of insert selectable in 45° steps
- with spreader claws

**Connection**

Connection terminals according to IEC 60884-1  
- with plug-in terminals

**Use**

- enhanced contact protection
- Mounting orientation variable in 45° steps

#### Safety

---

Protection index IP	IP20
IK protection code against mechanical impacts	05

---

- Enhanced contact protection

---

#### Identification

---

Main design line	Serie 1930/R.classic
Secondary design line(s)	Berker R.1, Berker R.3

---

#### Instructions

- 
- Specially suited for combining several socket outlets if right angle plugs are used.
  - Note:  
When integrating this product into the Serie 1930, the 1gang frame for centre plate Ø 58 mm, order no.: 1382 0... may only be used. Installation in multiple combinations of the Serie 1930 is not possible!
-