



SCHUKO S/outlet - Arsysis S/steel

47140004

Architecture

| | |
|--------|------------------------|
| Design | according to DIN 49440 |
|--------|------------------------|

Main electrical features

| | |
|---------------|----------|
| Rated current | 16 A |
| Rated voltage | 250 V AC |

Cover, door

| |
|-----------------------|
| - Central cover plate |
|-----------------------|

Materials

| | |
|------------------------|-----------------------------|
| RAL colour | RAL 9022 - Pearl light grey |
| Colour of design line | Stainless steel |
| Colour | stainless steel optics |
| Colour | stainless steel |
| Material / workmanship | metal, matt finish |
| Material | stainless steel |
| Surface appearance | matt |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

| |
|-----------------------|
| - with spreader claws |
|-----------------------|

Connection

| | |
|--------------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
| - with plug-in terminals | |

Safety

| | |
|-----------------------------------------------|------|
| Protection index IP | IP20 |
| IK protection code against mechanical impacts | 07 |
| - without enhanced contact protection | |

Identification

Main design line

Berker Arsys
