



SOCK.HIN.CO.PL-IN ARS.PW

47470069

Architecture

| | |
|--------|------------------------|
| Design | according to DIN 49440 |
|--------|------------------------|

Main electrical features

| | |
|---------------|----------|
| Rated current | 16 A |
| Rated voltage | 250 V AC |

Cover, door

- when opening hinged cover, it can be arrested in end position
- Central cover plate

Materials

| | |
|-----------------------|-----------------------|
| RAL colour | RAL 9010 - Pure white |
| Colour of design line | polar white |
| Colour | white |
| Colour | polarwhite |
| Material | duroplastic |
| Surface appearance | glossy |

Dimensions

| | |
|-----------------|-------|
| Insertion depth | 32 mm |
|-----------------|-------|

Installation, mounting

- mounting orientation of insert selectable in 45° steps
- with spreader claws

Connection

| | |
|----------------------|--------------------------|
| Connection terminals | according to IEC 60884-1 |
|----------------------|--------------------------|

- with plug-in terminals

Use

- enhanced contact protection
 - Mounting orientation variable in 45° steps
-

Safety

| | |
|---|------|
| Protection index IP | IP20 |
| IK protection code against mechanical impacts | 02 |

- Enhanced contact protection
-

Identification

| | |
|------------------|--------------|
| Main design line | Berker Arsys |
|------------------|--------------|

Instructions

- Specially suited for combining several socket outlets if right angle plugs are used.
-